Series 4800E

3-sectioned therapy table with electric motorized height adjustment

Model 4840-00E white powder coated (RAL 9010)
Model 4840-03E white aluminium powder coated (RAL 9006)
Model 4840-04E grey aluminium powder coated (RAL 9007)



German manufacture

All pictures:
Model 4840-00E
with options:
Wheel-lifting/fixing mechanism (045N),
surrounding foot control (095E),
head part 3-sectioned (055-10);
upholstery colour: 64-701 stone blue

Basic equipment:

- Lying surface 3-sectioned
- Multifunctional and independent adjustment of upholstery sections
- Possibilities of positioning the surface parts: Roof shape, Trendelenburg, reverse Trendelenburg
- Table not movable, including height adjustment screws to compensate for uneven ground
- High adjustment range
- Electromotive drive control by foot switch (option: hand switch)
- Integrated safety function for automatic blocking of electromotive drive
- Freewheeling downwards, automatic declutch in case of resistance
- Dewert-hygiene-equipment

Upholstery:

Lying surface 3-sectioned:

- Head part stepless up- (+45°) and downwards (-35°) adjustable by gas spring
- Length head part: 450 mm
- Head part with nose opening and upholstery part to close
- Middle part adjustable to roof position by gas spring
- Length middlepart: 530 mm
- Foot part stepless adjustable (+65°) to sitting position by 2 gas springs
- Length foot part: 1020 mm
- Thickness of upholstery: 60 mm

Technical data:

- Electronical height adjustment: 510 mm to 1030 mm in 18 sec.
  by AC-motor with a pressure capacity of 10000 N
- Width of lying surface: 700 mm
- Length of lying surface: 2000 mm
- Load capacity: 250 kg; according to IEC 60601 tested with fourfold static load

kg

Design:

2 different variants for artificial leather eligible for upholstery covering:

- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology



Available as an option (see pricelist for additional options)

Mobility

Art. no. 040N
Movable on comfort twin castors Ø 100 mm, each with total lock, basic height -15 mm

Art. no. 046
Movable on twin castors, Ø 100 mm with central lock, basic height +20 mm

Art. no. 045N
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering

Additional motor control options

Art. no. 090E
Hand switch (low voltage), with magnet on the back to fasten

Art. no. 091E
Foot switch (low voltage)

Art. no. 092E
1 foot switch fixation mounted at underframe

Art. no. 094E
Foot switch rail, lateral, on both sides, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered

Art. no. 095E
Foot switch rail, surround, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered

Additional safety options

Art. no. B1997E
Foot switch cover, made of brushed VA-steel

Paper roll holder

Art. no. 010K
Paper roll holder, mounted under head part (not protruding), for width 700 mm, not in case of 3-sectioned head part (Art. no. 056)

Art. no. 010F
Paper roll holder, mounted at foot part (protruding: 70 mm), for width 700 mm

Head part options

Art. no. 055-10
Head part 3-sectioned, arm rests downwards adjustable from -25° to +45° and removable
(art. no. 010K not possible)
measures:
Head part: L. 500 mm x W. 370 mm
Arm rests: L. 420 mm x W. 160 mm

Arm rests

without picture

Art. no. B088
1 arm rest, fixed, swivelling and removable, additional revolving and tiltable

Nose opening



Art. no. 1615-EF
Loss of nose opening and upholstery part to close

Upholstery options

Art. no. 007
Width of upholstery 800 mm

Art. no. B1772
Upholstery medium-soft (cold foam cover), for width 700 mm, thickness 70 mm

Updated 06.2022_01
changes concerning the technical data are subject to change