

German manufacture

Series 4000E

2-sectioned versatile treatment tables with electric motorized height adjustment

… for examination, treatment, therapy …

Model 4000-00E and 4001-00E white powder coated (RAL 9010)
Model 4000-03E and 4001-03E white aluminium powder coated (RAL 9006)
Model 4000-04E and 4001-04E silver aluminium powder coated (RAL 9007)

▶Model 4805-..E corresponds with model 4000-..E, but with nose opening



Electric motorized height adjustment



Table in highest position

All pictures:
Model 4000-00XLE
with options:
Wheel-lifting/fixing mechanism (1045N), without foot switch (1910E-EF), hand switch (1920E);
upholstery colour: 64-173 smaragd

Basic equipment:

- Table not movable, including height adjustment screws to compensate for uneven ground
- High adjustment range
- Electromotive drive control by foot switch (option: hand switch)
- Integrated safety function for automatic blocking of electromotive drive (art. no. 1999, mandatory equipment)
- Freewheeling downwards, automatic declutch in case of resistance
- Dewert-hygiene-equipment

Upholstery:

Lying surface 2-sectioned:

- Head part stepless up- (+40°) and downwards (-35°) adjustable by gas spring
- Length head part: 500 mm
- Fixed foot part
- Length foot part: 1500 mm
- Upholstery thickness: 60 mm





Table in lowest position

Technical data:

- Electronical height adjustment: 420 mm to 970 mm in 18 sec.
  by AC-motor with a pressure capacity of 10000 N
- Width of lying surface: Model 4000E: 700 mm | Model 4001E: 800 mm
- Length of lying surface: 2000 mm
- Load capacity: 250 kg; according to IEC 60601 tested with fourfold static load

kg

Design:

2 different variants for artificial leather eligible for upholstery covering:

- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology



vertical adjustment

Available as an option (see pricelist for additional options)

Mobility



Art. no. 1120N-10
Movable on comfort twin castors Ø 100 mm, each with total lock, basic height -15 mm



Art. no. 1180N
Movable on twin castors, Ø 100 mm with central lock, basic height +20 mm



Art. no. 1185
Movable on comfort twin castors, Ø 125 mm with central lock, basic height + 50 mm



Art. no. 1045N
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering

Additional motor control options



Art. no. 1920E
Hand switch (low voltage), with magnet on the back to fasten



Art. no. 1910E
Foot switch (low voltage)



Art. no. 1940E
1 foot switch fixation mounted at underframe



Art. no. 1950E
Foot switch rail, lateral, on both sides, security adjustment



Art. no. 1960E
Foot switch rail, surround, security adjustment

Paper roll holder



Art. no. 1270K / 1280K
Paper roll holder, mounted under head part (not protruding), for width 700 mm / 800 mm



Art. no. 1270F / 1280F
Paper roll holder, mounted at foot part (protruding: 70 mm), for width 700 mm / 800 mm

Nose opening



Art. no. 1610
Nose opening, in head part

Art. no. 1620
Upholstery part to close

Side guards



Art. no. 1080
1 side guard lateral lowerable, chromium-plated, completely made of steel tube, length: 1060 mm

Wall protection bumpers



Art. no. 1175 / 1176
4 wall protection bumpers Ø 150 mm, including mounting, for width 700 mm / 800 mm

Upholstery options

Art. no. 1770 / 1780
Soft covering for pleasant resting comfort, for width 700 mm / 800 mm, thickness 80 mm

Art. no. 1772 / 1782
Upholstery medium-soft (cold foam cover), for width 700 mm / 800 mm, thickness 70 mm

Updated 04.2023_01
changes concerning the technical data are subject to change