


German manufacture

Series DX1

2-sectioned versatile treatment tables with electric motorized height adjustment

...for examination, treatment, therapy…

Model 1000-00E white powder coated (RAL 9010)
Model 1000-03E white aluminium powder coated (RAL 9006)
Model 1000-04E grey aluminium powder coated (RAL 9007)





Modell 1000-00E
with basic equipment,
with hand switch;
upholstery colour: 64-717 deep sea

Basic equipment:

- Table not movable, including height adjustment screws to compensate for uneven ground
- Electromotive drive control by foot switch (option: hand switch)
- Integrated safety function for automatic blocking of electromotive drive
- Freewheeling downwards, automatic declutch in case of resistance
- Dewert-hygiene-equipment

Upholstery:

Lying surface 2-sectioned:

- Head part stepless up- (+40°) and downwards (-35°) adjustable by gas spring
- Length head part: 550 mm, integrated nose opening and upholstery part to close
- Fixed foot part
- Length foot part: 1400 mm
- Upholstery thickness: 65 mm



Modell 1000-04E mit options:
Wheel lifting/fixing mechanism (045N), paper roll holder (010F); upholstery colour: 64-173 smaragd

Technical data:

- Electronical height adjustment: 480 - 920 mm in 22 sec. by AC-motor with a pressure capacity of 10000 N
- Width overall: 700 mm
- Length overall: 1950 mm
- Load capacity: 225 kg, according to IEC 60601 tested with fourfold static load
  Load capacity head part: 90 kg

kg

Design:

2 different variants for artificial leather eligible for upholstery covering:

- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology



vertical
adjustment

Available as an option (see pricelist for additional options)

Mobility



Art. no. 040N
Movable on comfort twin castors Ø 100 mm, each with total lock, basic height -15 mm



Art. no. 046
Movable on twin castors, Ø 100 mm with central lock, basic height +20 mm



Art. no. B1185
Movable on comfort twin castors, Ø 125 mm with central lock, basic height + 50 mm



Art. no. 045N
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering

Additional motor control options



Art. no. 090E
Hand switch (low voltage), with magnet on the back to fasten



Art. no. 091E
Foot switch (low voltage)



Art. no. 092E
1 foot switch fixation mounted at underframe



Art. no. 094E
Foot switch rail, lateral, on both sides, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered



Art. no. 096E
Foot switch rail, surround, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered

Additional safety options



Art. no. B1997E
Foot switch cover, made of brushed VA-steel

Paper roll holder



Art. no. 010K/015K
Paper roll holder, mounted under head part (not protruding), for width 700 mm / 800 mm




Art. no. 010F/015F
Paper roll holder, mounted at foot part (protruding: 70 mm), for width 700 mm / 800 mm

Wall protection bumpers



Art. no. B1175 / B1176
4 wall protection bumpers Ø 150 mm, including mounting, for width 700 mm / 800 mm

Head part options



Art. no. 1615-EF
Loss of nose opening and upholstery part to close



Art. no. 056
Head part 3-sectioned, arm rests downwards adjustable and removable
(Art. no. 010K/015K not possible)

Side guards



Art. no. 1008
2 side guards lateral lowerable, RAL 9006 powder coated, made of steel tube, length: 820 mm

Upholstery options

Art. no. 006: Width 800 mm

Art. no. B1770 / B1788:
Soft covering for pleasant resting comfort, for width 700 mm/ 800 mm, thickness 80 mm

Art. no. B1772 / B1782:
Upholstery medium-soft (cold foam cover), for width 700 mm / 800 mm, thickness 70 mm

Updated 2022.1_01
Technical data are subject to change