


Series DX1

2-sectioned versatile treatment tables with electric motorized height adjustment

...for examination, treatment, therapy…

Model 1030-00E white powder coated (RAL 9010)
Model 1030-03E white aluminium powder coated (RAL 9006)
Model 1030-04E grey aluminium powder coated (RAL 9007)



NEW

German manufacture



Both pictures:
Model 1030-04E with options:
Movable on comfort twin castors, each with lock (040N);
upholstery colour: 64-703 pearl

Basic equipment:

- Table not movable, including height adjustment screws to compensate for uneven ground
- Long head part with half-round design
- Electromotive drive control by foot switch (option: hand switch)
- Integrated safety function for automatic blocking of electromotive drive
- Freewheeling downwards, automatic declutch in case of resistance
- Dewert-hygiene-equipment



Upholstery:

Lying surface 2-sectioned:

- Head part stepless adjustable from 0° to +75° by gas spring (sitting position)
- Length head part: 750 mm, without nose opening
- Fixed foot part
- Length foot part: 1200 mm
- Upholstery thickness: 65 mm



Technical data:

- Electronical height adjustment: 520 - 960 mm in 22 sec. by AC-motor with a pressure capacity of 10000 N
- Width overall: 700 mm
- Length overall: 1950 mm
- Load capacity: 225 kg, according to IEC 60601 tested with fourfold static load
  Load capacity head part: 90 kg


kg

Design:

2 different variants for artificial leather eligible for upholstery covering:

- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology





Available as an option (see pricelist for additional options)

DEWERT Präzisions-Stahlrohrmöbel

Mobility



Art. no. 040N
Movable on comfort twin castors Ø 100 mm, each with total lock, basic height -15 mm



Art. no. 046
Movable on twin castors, Ø 100 mm with central lock, basic height +20 mm



Art. no. B1185
Movable on comfort twin castors, Ø 125 mm with central lock, basic height + 50 mm



Art. no. 045N
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering

Additional motor control options



Art. no. 090E
Hand switch (low voltage), with magnet on the back to fasten



Art. no. 091E
Foot switch (low voltage)



Art. no. 092E
1 foot switch fixation mounted at underframe



Art. no. 094E
Foot switch rail, lateral, on both sides, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered



Art. no. 096E
Foot switch rail, surround, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered

Additional safety options



Art. no. B1997E
Foot switch cover, made of brushed VA-steel

Paper roll holder



Art. no. 010K/015K
Paper roll holder, mounted under head part (not protruding), for width 700 mm / 800 mm



Art. no. 010K/F / 015K/F
Paper roll holder, mounted at foot part (not protruding), for width 700 mm / 800 mm

Wall protection bumpers



Art. no. B1175 / B1176
4 wall protection bumpers Ø 150 mm, including mounting, for width 700 mm / 800 mm

Head part option



Art. no. 1615-EF
Loss of nose opening and upholstery part to close

Side guards



Art. no. 1008
2 side guards lateral lowerable, RAL 9006 powder coated, made of steel tube, length: 820 mm

Upholstery options

Art. no. 006: Width 800 mm

Art. no. B1770 / B1788:
Soft covering for pleasant resting comfort, for width 700 mm/ 800 mm, thickness 80 mm

Art. no. B1772 / B1782:
Upholstery medium-soft (cold foam cover), for width 700 mm / 800 mm, thickness 70 mm

Updated 2022.1_01
Technical data are subject to change