

Series 6000E

2-sectioned table with electric lifting column

… for examination, treatment

Model 6050-03E and 6051-03E white aluminium powder coated (RAL 9006)
Model 6050-04E and 6051-04E silver aluminium powder coated (RAL 9007)

▶Model 6810-..XLE corresponds with modell 6050-..XLE, but with nose opening





German manufacture

All pictures:
Model 6050-04XLE
with options:
Movable on twin castors
with central lock (1048),
paper roll holder (1270K/F);
upholstery colour:
64-715 anthracite

Basic equipment:

- Table not movable, including height adjustment screws to compensate for uneven ground
- Long head part with half-round design
- Electric motorized height adjustment by electric lifting column, arranged in the middle
- Electromotive drive control by foot switch (option: hand switch)
- Lying surface inclinable to 20° (Trendelenburg) by electromotive drive, operation by hand switch
- Integrated safety function for automatic blocking of electromotive drive
- Dewert-hygiene-equipment



Upholstery:

Lying surface 2-sectioned:

- Head part stepless up- (+75°) and downwards (-25°) adjustable by gas spring (sitting position)
- Length head part: 750 mm
- Fixed foot part
- Length foot part: 1200 mm
- Upholstery thickness: 60 mm

Technical data:


- Electronical height adjustment: 560 mm to 960 mm in 24 Sec.
  by integrated AC-motor with a pressure capacity of 3000 N
- Lying surface inclinable to 20° (Trendelenburg) by electromotive drive
- Width of lying surface: Model 6050-..E: 700 mm | Model 6051-..E: 800 mm
- Length of lying surface: 1950 mm
- Load capacity: 250 kg; according to IEC 60601 tested with fourfold static load

kg

Design:

2 different variants for artificial leather eligible for upholstery covering:

- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology



vertical
adjustment

Available as an option (see pricelist for additional options)

Mobility



Art. no. 1048
Movable on twin castors with central lock, Ø 100 mm, underpart lowered, basic height +20 mm



Art. no. 1047
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering, underpart lowered, basic height +20 mm

Additional motor control options



Art. no. 1920E
Hand switch (low voltage), with magnet on the back to fasten



Art. no. 1910E
1 foot switch (low voltage)

Additional safety options



Art. no. B1997E
Foot switch cover, made of brushed VA-steel

Paper roll holder



Art. no. 1270K / 1280K
Paper roll holder, mounted under head part (not protruding), for width 700 mm / 800 mm



Art. no. 1270K/F / 1280K/F
Paper roll holder, mounted at foot part (70 mm protruding), for width 700 mm / 800 mm

Nose opening



Art. no. 1610
Nose opening, in head part

Art. no. 1620
Upholstery part to close

Add-on elements



Art. no. 1410
1 piece of side rail, length: 350 mm



Art. no. 1430
1 attachment clamp for side rail, suitable for pipe: Ø 18 mm

Arm rests



Art. no. 1440
Arm rest for side rail, without attachment clamp, swivelling and removable, additional revolving and tiltable

Side guards



Art. no. 1080-60
1 side guard lateral lowerable, chromium-plated, completely made of steel tube, length: 820 mm



Art. no. 1005
1 side guard to fit on side rail, with attachment clamp, chromium-plated, length: 800 mm

Wall protection bumpers



Art. no. 1175 / 1176
4 wall protection bumpers Ø 150 mm, including mounting, for width 700 mm / 800 mm

Upholstery options

Art. no. 1770 / 1780
Soft covering for pleasant resting comfort, for width 700 mm / 800 mm, thickness 80 mm

Art. no. 1772 / 1782
Upholstery medium-soft (cold foam cover), for width 700 mm / 800 mm, thickness 70 mm

Updated 06.2022_01
changes concerning the technical data are subject to change