


Series 6000E

5-sectioned table with electric lifting column

… for examination, treatment

Model 6080-03E white aluminium powder coated (RAL 9006)
Model 6080-04E silver aluminium powder coated (RAL 9007)

▶Model 6880-..XLE corresponds with model 6080-..XLE



German manufacture

without picture

Basic equipment:

- Lying surface 5-sectioned, adjustment of all sections of lying surface is independent from height
- Foot parts almost vertical tiltable for good sitting position
- Table not movable, including height adjustment screws to compensate for uneven ground
- Electric motorized height adjustment by electric lifting column, arranged in the middle
- Electromotive drive control by foot switch (option: hand switch)
- Integrated safety function for automatic blocking of electromotive drive
- Dewert-hygiene-equipment

Upholstery:

Lying surface 5-sectioned:

- Head part stepless up- (+ 35°) and downwards (-30°) adjustable by gas spring
- Length head part: 360 mm, with nose opening and upholstery part to close
- Back part stepless up- (+ 70°) and downwards (-15°) adjustable by gas spring | Length back part: 570 mm
- By adjusting the back part, positioning of head part is changing as well
- Fixed seat part, length seat part: 460 mm
- Foot part: 2-sectioned, each leg part individually stepless adjustable (-85° - +20°) by gas spring, almost vertical tiltable, a good sitting position is possible | Length foot part: 550 mm, width foot part: 350 mm
- The upholstery is in aesthetic design with tapering from back part to end of head and foot part
- Upholstery thickness: 60 mm

Technical data:


- Electronical height adjustment: 620 mm to 1.020 mm in 24 Sec. by integrated AC-motor with a pressure capacity of 3000 N
- Width of lying surface: 700 mm
- Length of lying surface: 1950 mm
- Load capacity: 220 kg; according to IEC 60601 tested with fourfold static load


kg

Design:

2 different variants for artificial leather eligible for upholstery covering:

- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology





Available as an option (see pricelist for additional options)

Mobility



Art. no. 1048
Movable on twin castors with central lock, Ø 100 mm, underpart lowered, basic height +20 mm



Art. no. 1047
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering, underpart lowered, basic height +20 mm

Additional motor control options



Art. no. 1920E
Hand switch (low voltage), with magnet on the back to fasten



Art. no. 1910E
1 foot switch (low voltage)

Additional safety options




Art. no. B1997E
Foot switch cover, made of brushed VA-steel

Paper roll holder



Art. no. 1270K
Paper roll holder, mounted under head part (not protruding), for width 700 mm

Nose opening



Art. no. 1615-EF
Loss of nose opening and upholstery part to close

Upholstery options

Art. no. 1770
Soft covering for pleasant resting comfort, for width 700 mm, thickness 80 mm

Art. no. 1772
Upholstery medium-soft (cold foam cover), for width 700 mm, thickness 70 mm

Add-on elements



Art. no. 1410
1 piece of side rail



Art. no. 1430
1 attachment clamp for side rail, suitable for pipe: Ø 18 mm

Arm rests



Art. no. 1440
Arm rest for side rail, without attachment clamp, swivelling and removable, additional revolving and tiltable

Side guards



Art. no. 1005
1 side guard to fit on side rail, with attachment clamp, chromium-plated, length: 800 mm

Foot part options



Art. no. G101
1-sectioned foot part

Updated 06.2022_01
changes concerning the technical data are subject to change