


Series 6000E

5-sectioned table with electric lifting column

… for examination, treatment

Model 6085-03E white aluminium powder coated (RAL 9006)
Model 6085-04E silver aluminium powder coated (RAL 9007)
▶Model 6885-..XLE corresponds with model 6085-..XLE



German manufacture



Model 6085-04XLE, blue:
with options: Movable on comfort twin castors with central lock (1048);
upholsery colour: 64-174 sky



Model 6085-04XLE, grey:
with options: Movable on comfort twin castors with central lock (1048),
1-sectioned foot part (G101);
upholstery colour:
64-712 sate grey



Basic equipment:

- Lying surface 5-sectioned, adjustment of all sections of lying surface is independent from height
- Foot parts almost vertical tiltable for good sitting position
- Table not movable, including height adjustment screws to compensate for uneven ground
- Electric motorized height adjustment by electric lifting column, arranged in the middle
- Electromotive drive control by foot switch (option: hand switch)
- Lying surface inclinable to 12° (Trendelenburg) by electromotive drive, operation by hand switch
- Integrated safety function for automatic blocking of electromotive drives
- Dewert-hygiene-equipment



Upholstery:

Lying surface 5-sectioned:

- Head part stepless up- (+ 35°) and downwards (-30°) adjustable by gas spring
- Length head part: 360 mm, with nose opening and upholstery part to close
- Back part stepless up- (+ 70°) and downwards (-15°) adjustable by gas spring | Length back part: 570 mm
- By adjusting the back part, positioning of head part is changing as well
- Fixed seat part, length seat part: 460 mm
- Foot part: 2-sectioned, each leg part individually stepless adjustable (-85° - +20°) by gas spring, almost vertical tiltable, a good sitting position is possible | Length foot part: 550 mm, width foot part: 350 mm
- The upholstery is in aesthetic design with tapering from back part to end of head and foot part
- Upholstery thickness: 60 mm

Technical data:

- Electronical height adjustment: 620 mm to 1020 mm in 24 Sec. by integrated AC-motor with a pressure capacity of 3000 N
- Lying surface inclinable to 12° (Trendelenburg) by electromotive drive
- Width of lying surface: 700 mm | Length of lying surface: 1950 mm
- Load capacity: 220 kg; according to IEC 60601 tested with fourfold static load


kg

Design:

2 different variants for artificial leather eligible for upholstery covering:

- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology





Available as an option (see pricelist for additional options)

DEWERT Präzisions-Stahlrohrmöbel

Mobility



Art. no. 1048
Movable on twin castors with central lock, Ø 100 mm, underpart lowered, basic height +20 mm



Art. no. 1047
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering, underpart lowered, basic height +20 mm

Additional motor control options



Art. no. 1920E
Hand switch (low voltage), with magnet on the back to fasten




Art. no. 1910E
1 foot switch (low voltage)

Additional safety options



Art. no. B1997E
Foot switch cover, made of brushed VA-steel

Nose opening



Art. no. 1615-EF
Loss of nose opening and upholstery part to close

Upholstery options

Art. no. 1770
Soft covering for pleasant resting comfort, for width 700 mm, thickness 80 mm

Art. no. 1772
Upholstery medium-soft (cold foam cover), for width 700 mm, thickness 70 mm

Add-on elements



Art. no. 1410
1 piece of side rail



Art. no. 1430
1 attachment clamp for side rail, suitable for pipe: Ø 18 mm

Arm rests



Art. no. 1440
Arm rest for side rail, without attachment clamp, swivelling and removable, additional revolving and tiltable

Side guards



Art. no. 1005
1 side guard to fit on side rail, with attachment clamp, chromium-plated, length: 800 mm

Foot part options



Art. no. G101
1-sectioned foot part

Updated 06.2022_01
changes concerning the technical data are subject to change