


Series 2800XL

3-sectioned therapy table with electric motorized height adjustment

Model 2830-00XLE white powder coated (RAL 9010)
Model 2830-03XLE white aluminium powder coated (RAL 9006)
Model 2830-04XLE grey aluminium powder coated (RAL 9007)



German manufacture









All pictures: Model 2830-00XLE with options:
Wheel-lifting/fixing mechanism (045N), surrounding foot switch rail (095E), 3-sectioned head part (056);
upholstery colour: 64-716 black

Basic equipment:

- Lying surface 3-sectioned
- Middle part stepless adjustable to roof position, Trendelenburg position possible
- Table not movable, including height adjustment screws to compensate for uneven ground
- Electromotive drive control by foot switch (option: hand switch)
- Integrated safety function for automatic blocking of electromotive drive
- Freewheeling downwards, automatic declutch in case of resistance
- Dewert-hygiene-equipment



Upholstery:

Lying surface 3-sectioned:

- Head part stepless up- (+45°) and downwards (-40°) adjustable by gas spring
- Length head part: 540 mm; with nose opening and upholstery part to close
- Middle part upwards manually adjustable to roof position, supported by 2 gas springs, due to 2 guide rods which are fixed by screwing a clamping lever, this adjustment system is without clearance
- Length middle part: 470 mm
- Foot part stepless adjustable (+70°) by a self-fixing system of 2 guide rods, without clearance
- Length foot part: 940 mm
- Thickness of upholstery: 60 mm

Technical data:

- Electronical height adjustment: 510 mm to 950 mm in 22 sec. by AC-motor with a pressure capacity of 10000 N
- Width of lying surface: 700 mm
- Length of lying surface: 1950 mm
- Load capacity: 250 kg; according to IEC 60601 tested with fourfold static load

kg

Design:

2 different variants for artificial leather eligible for upholstery covering:


- Skai® Pandoria Plus with velvet-smooth surface
- Skai® Toronto EN with innovative staynu-technology





Available as an option (see pricelist for additional options)

Mobility



Art. no. 040N
Movable on comfort twin castors Ø 100 mm, each with total lock, basic height -15 mm



Art. no. 046
Movable on twin castors, Ø 100 mm with central lock, basic height +20 mm



Art. no. 045N
Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering

Additional motor control options



Art. no. 090E
Hand switch (low voltage), with magnet on the back to fasten



Art. no. 091E
Foot switch (low voltage)




Art. no. 092E
1 foot switch fixation mounted at underframe



Art. no. 094E
Foot switch rail, lateral, on both sides, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered



Art. no. 095E
Foot switch rail, surround, security adjustment:
Press the switch rail down = the table is lifted
Lift the switch rail up = the table is lowered



Art. no. 065E
Electric motorized adjustment to roof position

Paper roll holder



Art. no. 010K
Paper roll holder, mounted under head part (not protruding), for width 700 mm, not in case of 3-sectioned head part (Art. no. 056)




Art. no. 010K/F
Paper roll holder, mounted at foot part (not protruding), for width 700 mm

Head part options



Art. no. 056
Head part 3-sectioned, arm rests downwards adjustable from -25° to +45° and removable (art. no. 010K not possible)
measures:
Head part: L. 540 mm x W. 370 mm
Arm rests: L. 500 mm x W. 160 mm

Nose opening



Art. no. 1615-EF
Loss of nose opening and upholstery part to close

Arm rests

without picture

Art. no. 088
1 arm rest, fixed, swivelling and removable, additional revolving and tiltable

Upholstery options

Art. no. 007
Width of upholstery 800 mm

Art. no. B1772
Upholstery medium-soft (cold foam cover), for width 700 mm, thickness 70 mm

Updated 04.2023_01
changes concerning technical data are subject to change